



9894 AIR BRAKE-FLUID DOT-4

Description

Brake and Clutch Fluid DOT 4 is a high performance non-petroleum automotive brake fluid designed for conventional hydraulic brake and clutch systems. Brake and Clutch Fluid DOT 4 is formulated for use under severe operating conditions or where DOT 4 fluids are recommended. Brake and Clutch Fluid DOT 4 combines a complex combination of Polyglycols, Polyglycol Ethers and Glycol Ether Borate Esters, blended with inhibitors designed to prevent corrosion, oxidation and to control seal swell characteristics.


Features

- Higher and maintained fluid boiling point in service promotes lower vapour formation and greater braking performance than DOT 3.
- Designed to aid vapour lock prevention, offering greater braking safety margin than lower specification fluids.
- Formulated for use in a wide range of conventional systems, reducing inventories and costs.

Characteristics

Colour	Amber
pH value	8.3
cSt @ 100°C	3.2
Equilibrium Reflux Boiling Point, °C	251
Wet Equilibrium Reflux Boiling Point, °C	160
cSt @ 40°C	1296

*The typical characteristics mentioned represent mean value.



Health & Safety

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

SILBOIL LUBRICANTS (INDIA)

Plot No. 6, Dan Udyog Industrial Estate, Piparia, Silvassa- 396230
Union Territory of Dadra & Nagar Haveli, INDIA

This lubricant used in accordance with our recommendations and for the applications for which it is intended does not represent a special hazard. A Safety data file conforming to the requirements of current Indian legislation is available from your local trade consultant.

For more information, go to www.silboil.com, For technical or consumer support mail us at info@silboil.com or call us at + (91)- 7500-67-111

