



CLASSIC MG-SPECIAL 25W- 50 API CH-4/SL

Description

Silboil Classic MG- Special is a high viscosity, high performance engine oil that provides proven protection for diesel engines operating in severe service applications. Special 25W- 50 is recommended for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Features

- ◆ Thermal and oxidation stability.
- ◆ Controls sludge build-up and deposits.
- ◆ Deposit control and acid neutralization.
- ◆ Longer gasket and seal life.
- ◆ Component compatibility.

Characteristics

SAE Grade	25W- 40
Viscosity Index, ASTM D 2270	113
cSt @ 40°C	101
Total Base #, mg/KOH/g	8.4
Pour Point, °C	-27
Flash Point, °C, ASTM D 92	237

*The typical characteristics mentioned represent mean value.



Health & Safety

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

SILBOIL LUBRICANTS (INDIA)

Plot No. 6, Dan Udyog Industrial Estate, Piparia, Silvassa- 396230
Union Territory of Dadra & Nagar Haveli, INDIA

This lubricant used in accordance with our recommendations and for the applications for which it is intended does not represent a special hazard. A Safety data file conforming to the requirements of current Indian legislation is available from your local trade consultant.

For more information, go to www.silboil.com, For technical or consumer support mail us at info@silboil.com or call us at +(91)- 7500-67-111

