



## DSG- DIRECT SHIFT GEAR BOX OIL 80W- 90 GL-5

### Description

Silboil DSG 80W- 90 GL-5 is multigrade gear oil containing extreme pressure additives for moderate condition service Meets API GL -5, MIL - L - 2105 B and EP Type GL - 5 level of IS: 1118:1992 (Re-affirmed 2008) Application areas are synchromesh transmissions and manual transmissions of automobiles.

### Features

- Excellent thermal & chemical stability.
- Protection against rust & corrosion.
- Excellent trouble free operation.

### Characteristics

SAE GRADE	80W- 90
Viscosity Index, ASTM D 2270	90
cSt @ 100°C	13.5- 24.5
Copper Strip Corrosion at 121, °C	2
Pour Point, °C	-21
Flash Point, °C, ASTM D 92	165

\*The typical characteristics mentioned represent mean value.



### Health & Safety

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

### SILBOIL LUBRICANTS (INDIA)

Plot No. 6, Dan Udyog Industrial Estate, Piparia, Silvassa- 396230  
Union Territory of Dadra & Nagar Haveli, INDIA

This lubricant used in accordance with our recommendations and for the applications for which it is intended does not represent a special hazard. A Safety data file conforming to the requirements of current Indian legislation is available from your local trade consultant.

For more information, go to [www.silboil.com](http://www.silboil.com), For technical or consumer support mail us at [info@silboil.com](mailto:info@silboil.com) or call us at +(91)- 7500-67-111

