



FAVORIT PLUS-START 15W- 40 API SL/CF-4

Description

Silboil Favorit Plus- Start 15W- 40 is a modern high technology based engine oil exceeding the latest API SL performance specification. Developed to provide maximum protection for use in modern passenger cars including low emission engines and high performance vehicles. It is suitable for all types of driving conditions (city, highway and harsh) and is available in a range of SAE viscosity grades, to meet market conditions. Compatible for all cars running on lead free gasoline and catalytic converters.

Features

- Helps to extent life for critical engine parts.
- Long engine life.
- Helps to extend piston life.
- Outstanding overall engine cleanliness.

Characteristics

SAE GRADE	15W- 40
API Performance	SL/CF-4
Viscosity Index, ASTM D 2270	150
cSt @ 100°C	13.2 to 14.0
Total Base #, mg/KOH/g	8.2
Pour Point, °C	-12
Flash Point, °C, ASTM D 92	180

*The typical characteristics mentioned represent mean value.



Health & Safety

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

SILBOIL LUBRICANTS (INDIA)

Plot No. 6, Dan Udyog Industrial Estate, Piparia, Silvassa- 396230
Union Territory of Dadra & Nagar Haveli, INDIA

This lubricant used in accordance with our recommendations and for the applications for which it is intended does not represent a special hazard. A Safety data file conforming to the requirements of current Indian legislation is available from your local trade consultant.

For more information, go to www.silboil.com, For technical or consumer support mail us at info@silboil.com or call us at + (91)- 7500-67-111

