



OPTIMUM MG-SAFARI 20W- 40 API CF-4/SJ

Description

Silboil Safari CF4 20W40 is designed as superior quality multigrade long drain crankcase oil for gasoline as well as diesel engines. It is blended from selected base stocks and fortified with proprietary additive system to meet the performance level for different standards. It has strong built in alkaline reserve to combat corrosive wear associated with the use of high sulphur fuels.

Features

- ◆ Resists formation of hard piston deposits and varnish at high operating temperatures.
- ◆ Reduces soft sludge formation associated with low engine temperatures in periodically idling conditions.
- ◆ High protection against wear insuring maximum equipment life.
- ◆ Extends oil drain period due to enhanced dispersancy.

Characteristics

SAE Grade	20W- 40
Viscosity Index, ASTM D 2270	115
cSt @ 100°C	15.0 to 16.0
Total Base #, mg/KOH/g	9.0
Pour Point, °C	-21
Flash Point, °C, ASTM D 92	215

*The typical characteristics mentioned represent mean value.



Health & Safety

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

SILBOIL LUBRICANTS (INDIA)

Plot No. 6, Dan Udyog Industrial Estate, Piparia, Silvassa- 396230
Union Territory of Dadra & Nagar Haveli, INDIA

This lubricant used in accordance with our recommendations and for the applications for which it is intended does not represent a special hazard. A Safety data file conforming to the requirements of current Indian legislation is available from your local trade consultant.

For more information, go to www.silboil.com, For technical or consumer support mail us at info@silboil.com or call us at +(91)- 7500-67-111

