



POWER 2T-SPECIAL API TC/FB

Description

Silboil Power 2T is an advanced performance two-stroke engine oil developed to meet or exceed the highest level of lubricant requirements by today's highest performance motorcycles, snowmobiles and lean oil/fuel ratio chain saws and other two-stroke applications.

Features

- ◆ Helps to extent life for critical engine parts.
- ◆ Long engine life.
- ◆ Helps to extend piston life.
- ◆ Outstanding overall engine cleanliness.

Characteristics

| | |
|------------------------------|-------------|
| SAE Grade | Grade- 1, 2 |
| Viscosity Index, ASTM D 2270 | 154 |
| cSt @ 40°C | 12.7 |
| Total Base #, mg/KOH/g | 5.0 |
| Pour Point, °C | -42 |
| Flash Point, °C, ASTM D 92 | 100 |

*The typical characteristics mentioned represent mean value.



Health & Safety

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

SILBOIL LUBRICANTS (INDIA)

Plot No. 6, Dan Udyog Industrial Estate, Piparia, Silvassa- 396230
Union Territory of Dadra & Nagar Haveli, INDIA

This lubricant used in accordance with our recommendations and for the applications for which it is intended does not represent a special hazard. A Safety data file conforming to the requirements of current Indian legislation is available from your local trade consultant.

For more information, go to www.silboil.com, For technical or consumer support mail us at info@silboil.com or call us at +(91)- 7500-67-111

