



## PRIDE ULTRA-DIESEL 15W- 40 API CI-4/SM

### Description

Silboil Diesel 15W- 40 is a multi-grade engine oil with mineral and synthetic basis for high-augmented diesel engines of passenger cars and trucks with turbocharge. Perfectly balanced additives effectively protect from wear-out and prevent corrosion. Reduces scooting and carbon formation. Provides safe lubrication and engine cleanness at any usage conditions.

### Features

- ◆ High thermal and oxidation stability.
- ◆ Stay-in-grade shear stability.
- ◆ Improved scoot handling.
- ◆ Start-up wear protection.
- ◆ Improved viscosity control and used oil pumpability.

### Characteristics

SAE Grade	15W- 40
Viscosity Index, ASTM D 2270	132
cSt @ 40°C	112
Total Base #, mg/KOH/g	10.0
Pour Point, °C	-35
Flash Point, °C, ASTM D 92	221

\*The typical characteristics mentioned represent mean value.



### Health & Safety

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

### SILBOIL LUBRICANTS (INDIA)

Plot No. 6, Dan Udyog Industrial Estate, Piparia, Silvassa- 396230  
Union Territory of Dadra & Nagar Haveli, INDIA

This lubricant used in accordance with our recommendations and for the applications for which it is intended does not represent a special hazard. A Safety data file conforming to the requirements of current Indian legislation is available from your local trade consultant.

For more information, go to [www.silboil.com](http://www.silboil.com), For technical or consumer support mail us at [info@silboil.com](mailto:info@silboil.com) or call us at +(91)- 7500-67-111

