

SILBOIL PRODUCT DATA SHEET

FLEET MASTER-GREEN 15W- 40 CI-4+/SM

Description:

Fleet Master Genuine CI-4 PLUS Oil 15W-40 GREEN is an extra high performance diesel engine oil that provides excellent lubrication of today's diesel engines promoting extended engine life. This extra high performance has been proven in the field in a wide variety of industries, applications, and mixed fleets.

Features:

- High thermal and oxidation stability.
- Stay-in-grade shear stability.
- Improved scoot handling.
- Start-up wear protection.
- Improved viscosity control and used oil pumpability.

Characteristics:

SILBOIL FLEET MASTER-GREEN 15W- 40 CI-4 PLUS/SM	
SAE Grade	15W- 40
Viscosity Index, ASTM D 2270	137
cSt @ 40°C	109
Total Base #, mg/KOH/g	11
Pour Point, °C	-39
Flash Point, °C, ASTM D 92	226

Available Packs:

15 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

PRIDE ULTRA-DIESEL 15W- 40 CI-4/SM

Description:

Silboil Diesel 15W- 40 is a multi-grade engine oil with mineral and synthetic basis for high-augmented diesel engines of passenger cars and trucks with turbocharge. Perfectly balanced additives effectively protect from wear-out and prevent corrosion. Reduces scooting and carbon formation. Provides safe lubrication and engine cleanness at any usage conditions.

Features:

- High thermal and oxidation stability.
- Stay-in-grade shear stability.
- Improved scoot handling.
- Start-up wear protection.
- Improved viscosity control and used oil pumpability.

Characteristics:

SILBOIL PRIDE ULTRA-DIESEL 15W- 40 CI-4/SM	
SAE Grade	15W- 40
Viscosity Index, ASTM D 2270	132
cSt @ 40°C	112
Total Base #, mg/KOH/g	10.0
Pour Point, °C	-35
Flash Point, °C, ASTM D 92	221

Available Packs:

1 Ltr, 5 Ltr, 6 Ltr, 7.5 Ltr, 10 Ltr, 20 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

SUPER SONIC-STATIC 15W- 40 CF-4/SL

Description:

Silboil Static 15W- 40 is a multi-grade engine oil with mineral basis for high-augmented diesel engines of passenger cars and trucks with turbocharge. Perfectly balanced additives effectively protect from wear-out and prevent corrosion. Reduces scooting and carbon formation. Provides safe lubrication and engine cleanness at any usage conditions.

Features:

- High thermal and oxidation stability.
- Stay-in-grade shear stability.
- Improved scoot handling.
- Start-up wear protection.
- Improved viscosity control and used oil pumpability.

Characteristics:

SILBOIL SUPER SONIC-STATIC 15W- 40 CF-4/SL	
SAE Grade	15W- 40
Viscosity Index, ASTM D 2270	125
cSt @ 40°C	102
Total Base #, mg/KOH/g	8.5
Pour Point, °C	-32
Flash Point, °C, ASTM D 92	216

Available Packs:

1 Ltr, 5 Ltr, 6 Ltr, 7.5 Ltr, 10 Ltr, 20 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

OPTIMUM MG-SAFARI 20W- 40 CF-4/SJ

Description:

Silboil Safari CF4 20W40 is designed as superior quality multigrade long drain crankcase oil for gasoline as well as diesel engines. It is blended from selected base stocks and fortified with proprietary additive system to meet the performance level for different standards. It has strong built in alkaline reserve to combat corrosive wear associated with the use of high sulphur fuels.

Features:

- Resists formation of hard piston deposits and varnish at high operating temperatures.
- Reduces soft sludge formation associated with low engine temperatures in periodically idling conditions.
- High protection against wear insuring maximum equipment life.
- Extends oil drain period due to enhanced dispersancy

Characteristics:

SILBOIL OPTIMUM MG-SAFARI 20W- 40 CF-4/SJ	
SAE Grade	20W- 40
Viscosity Index, ASTM D 2270	115
cSt @ 100°C	15.0 to 16.0
Total Base #, mg/KOH/g	9.0
Pour Point, °C	-21
Flash Point, °C, ASTM D 92	215

Available Packs:

500 ML, 1 Ltr, 5 Ltr, 6 Ltr, 7.5 Ltr, 10 Ltr, 20 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

CLASSIC MG-SPECIAL 25W- 50 CH-4/SL

Description:

Silboil Classic MG- Special is a high viscosity, high performance engine oil that provides proven protection for diesel engines operating in severe service applications. Special 25W-50 is recommended for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Features:

- Thermal and oxidation stability.
- Controls sludge build-up and deposits.
- Deposit control and acid neutralization.
- Longer gasket and seal life.
- Component compatibility.

Characteristics:

SILBOIL CLASSIC MG-SPECIAL 25W- 50 CH-4/SL	
SAE Grade	25W- 50
Viscosity Index, ASTM D 2270	113
cSt @ 40°C	101
Total Base #, mg/KOH/g	8.4
Pour Point, °C	-27
Flash Point, °C, ASTM D 92	237

Available Packs:

500 ML, 1 Ltr, 7.5 Ltr, 10 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

PUMP SHAKTI-AGRI 20W- 40 CD

Description:

Silboil Pump Shakti- Agri is a good quality Engine oil specially designed for agricultural Pump-set diesel engines running on Diesel, Kerosene or Light Diesel Oil (LDO). Recommended for all types of Pump-sets. The product is also suitable for other Agricultural and Farm Equipment like Tractors, Power tillers, harvesters etc.

Features:

- Offers better fuel efficiency.
- Easy starting even at lower ambient temperatures.
- Higher level of engine cleanliness.
- Start-up wear protection.
- Longer oil life & equipment life.

Characteristics:

SILBOIL PUMP SHAKTI-AGRI 20W- 40 CD	
SAE Grade	20W- 40
Viscosity Index, ASTM D 2270	110
cSt @ 100°C	13.5 to 16.5
Total Base #, mg/KOH/g	4.19
Pour Point, °C	-21
Flash Point, °C, ASTM D 92	200

Available Packs:

1 Ltr, 1.5 Ltr, 2 Ltr, 3.5 Ltr, 4 Ltr, 5 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

TRACTOR GUARD-SPECIAL 20W- 40 CH-4

Description: Silboil Tractor Guard CH4 20W40 is designed as superior quality multigrade long drain crankcase oil for petrol as well as diesel engines. It is blended from selected base stocks and fortified with proprietary additive system to meet the performance level for different standards. It has strong built in alkaline reserve to combat corrosive wear associated with the use of high sulphur fuels.

Features:

- Resists formation of hard piston deposits and varnish at high operating temperatures.
- Reduces soft sludge formation associated with low engine temperatures in periodically idling conditions.
- High protection against wear insuring maximum equipment life.
- Extends oil drain period due to enhanced dispersancy.

Characteristics:

SILBOIL TRACTOR GUARD-SPECIAL 20W- 40 CH-4	
SAE Grade	20W- 40
Viscosity Index, ASTM D 2270	115
cSt @ 100°C	15.0 to 16.0
Total Base #, mg/KOH/g	9.0
Pour Point, °C	-21
Flash Point, °C, ASTM D 92	215

Available Packs:

6 Ltr, 7.5 Ltr, 10 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

S-TRANS UTTO & WET BRAKE OIL 20W JDJ21A

Description:

It is a premium quality of multipurpose universal tractor transmission oil which is blended from high quality hydro cracked base oils. The product is doped with tailor made additives specifically used for wet brake, hydraulic, clutch & transmission system in today's farm tractors & construction machinery.

Features:

- Excellent detergency & balanced friction system for imparting friction stability to tractor oils
- Superior pump wear / Abrasion.
- Advanced final drive performance.
- Noise free & efficient braking.

Characteristics:

SILBOIL S-TRANS 20W JDJ21A	
SAE Grade	20W- 40
Viscosity Index, ASTM D 2270	110
cSt @ 100°C	11.0 to 14.0
Copper Strip Corrosion 3hrs	1b
Pour Point, °C	-18
Flash Point, °C, ASTM D 92	210

Available Packs:

5 Ltr, 10 Ltr, 20 Ltr, 26 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

ADVANCED 4T-PLUS 10W- 50 SN/MA-2

Description:

Silboil Advanced 4T-Plus is a premium performance 4 Stroke Motorcycle Oil, engineered to enhance the performance of the new generation Transportation and Power Bikes. It is specially formulated with premium quality base oils and state of the art additive technology to provide excellent service under all conditions of use. Improved shear stability and high temperature viscosity control will ensure excellent protection of the engine and gear box.

Features:

- Low traction coefficient Ester to minimize engine internal friction losses and improve performance.
- Synergy of Ester with anti-wear additives and improved shear resistance for improved gear protection and life time.

Characteristics:

SILBOIL ADVANCED 4T- PLUS 10W- 50 SN/MA-2	
SAE Grade	10W- 50
Viscosity Index, ASTM D 2270	167
cSt @ 100°C	18.1
Total Base #, mg/KOH/g	8.5
Pour Point, °C	-33
Flash Point, °C, ASTM D 92	232

Available Packs:

900 ML, 1 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

BULLET SPECIAL 4T- SUPER 15W- 50 SM/MA-2

Description:

Silboil Bullet Special 4T 15W-50 is a premium quality engine oil specially formulated for high speed air-cooled and liquid cooled engines of new generation motorcycles. It is blended from superior quality base stocks and specially formulated additives that exceed the most demanding lubrication requirements and prevent degradation of the oil by damage-causing free radicals, thus ensuring optimum power retention, ride after ride.

Features:

- Exceptional anti-wear properties protect vital engine and gear components leading to reduced maintenance costs.
- Controlled frictional properties eliminate clutch slippage leading to increased power/ fuel economy and improves drivability.
- Active cleaning agents provide engine cleanliness

Characteristics:

SILBOIL BULLET SPECIAL 4T- SUPER 15W- 50 SM/MA-2	
SAE Grade	15W- 50
Viscosity Index, ASTM D 2270	145
cSt @ 100°C	17.1
Total Base #, mg/KOH/g	8.2
Pour Point, °C	-31
Flash Point, °C, ASTM D 92	227

Available Packs:

2.5 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

SUPREME 4T- QWICK 20W- 50 SM/MA-2

Description:

Silboil Supreme 4t- Qwick is a premium quality 4-stroke engine oils developed specifically to meet the requirements of the latest high performance air cooled 4-stroke bike engines. These oils are blended from superior quality base oils and specially selected performance additives.

Features:

- Low traction coefficient Ester to minimize engine internal friction losses and improve performance.
- Synergy of Ester with anti-wear additives and improved shear resistance for improved gear protection and life time.

Characteristics:

SILBOIL SUPREME 4T- QWICK 20W- 50 SM/MA-2	
SAE Grade	20W- 50
Viscosity Index, ASTM D 2270	165
cSt @ 100°C	16.7
Total Base #, mg/KOH/g	8.3
Pour Point, °C	-31
Flash Point, °C, ASTM D 92	229

Available Packs:

900 ML, 1 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

TWIN 4T- START 20W- 40 SM/TC MA-2

Description:

Silboil Twin 4T- Start 20W-40 is blended from highly base- stocks with special additive offers extra high performance to impart high oxidation stability, reduce fuel consumption, gear anti-wear, extreme pressure properties, sludge and varnish control. Keeps engine clean and long duration intervals.

Features:

- Exceptional anti-wear properties protect vital engine and gear components leading to reduced maintenance costs.
- Controlled frictional properties eliminate clutch slippage leading to increased power/ fuel economy and improves drivability.
- Active cleaning agents provide engine cleanliness

Characteristics:

SILBOIL TWIN 4T- START 20W- 40 SM/TC MA-2	
SAE Grade	20W- 40
Viscosity Index, ASTM D 2270	115
cSt @ 100°C	12.5 to 16.5
Total Base #, mg/KOH/g	7.0
Pour Point, °C	-21
Flash Point, °C, ASTM D 92	210

Available Packs:

900 ML, 1 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

ENDURANCE 4T- SELF 20W- 40 SL MA/MA-2

Description:

Silboil Endurance 4t- Self is blended from highly base- stocks with special additive offers extra high performance to impart high oxidation stability, reduce fuel consumption, gear anti-wear, extreme pressure properties, sludge and varnish control. Keeps engine clean and long duration intervals.

Features:

- Maximum power output.
- Superior performance in terms of oxidation stability.
- Excellent wear protection at high temperatures and severe operating conditions.
- Outstanding overall engine cleanliness.

Characteristics:

SILBOIL ENDURANCE 4T- SELF 20W- 40 SL MA/MA-2	
SAE Grade	20W- 40
Viscosity Index, ASTM D 2270	115
cSt @ 100°C	12.5 to 16.1
Total Base #, mg/KOH/g	7.0
Pour Point, °C	-31
Flash Point, °C, ASTM D 92	229

Available Packs:

900 ML, 1 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

UNIVERSAL 4T- PLUS 20W- 40 SL MB/MA-2

Description:

Silboil Universal 4T- Plus 20W-40 is blended from highly base- stocks with special additive offers extra high performance to impart high oxidation stability, reduce fuel consumption, gear anti-wear, extreme pressure properties, sludge and varnish control. Keeps engine clean and long duration intervals.

Features:

- Exceptional anti-wear properties protect vital engine and gear components leading to reduced maintenance costs.
- Controlled frictional properties eliminate clutch slippage leading to increased power/ fuel economy and improves drivability.
- Active cleaning agents provide engine cleanliness.

Characteristics:

SILBOIL UNIVERSAL 4T- PLUS 20W- 40 SL MB/MA-2	
SAE Grade	20W- 40
Viscosity Index, ASTM D 2270	115
cSt @ 100°C	12.5 to 15.5
Total Base #, mg/KOH/g	6.0
Pour Point, °C	-20
Flash Point, °C, ASTM D 92	205

Available Packs:

900 ML, 1 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

TORNADO 4T- FURIOUS 10W- 30 SM/MA-2

Description:

Silboil Tornado 4T- Furious is blended from highly base- stocks with special additive offers extra high performance to impart high oxidation stability, reduce fuel consumption, gear anti-wear, extreme pressure properties, sludge and varnish control. Keeps engine clean and long duration intervals.

Features:

- Maximum power output.
- Superior performance in terms of oxidation stability.
- Excellent wear protection at high temperatures and severe operating conditions.
- Outstanding overall engine cleanliness.

Characteristics:

SILBOIL TORNADO 4T- FURIOUS 10W- 30 SM/MA-2	
SAE Grade	10W- 30
Viscosity Index, ASTM D 2270	115
cSt @ 100°C	10.8
Total Base #, mg/KOH/g	7.0
Pour Point, °C	-30
Flash Point, °C, ASTM D 92	226

Available Packs:

900 ML, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

SCOOTY SPECIAL 4T- NITRIC 10W- 30 SM/MB

Description:

Silboil Scooty Special 4T- Nitric is specially designed for automatic scooters and gearless 2-wheelers. Its exclusive and unique formulation does not let the oil film break easily, thereby providing superior protection even in heavy traffic 'stop-n-go' conditions. This leads to a distinctly superior performance, which can be felt from the first use itself.

Features:

- Exceptional anti-wear properties protect vital engine and gear components leading to reduced maintenance costs.
- Controlled frictional properties eliminate clutch slippage leading to increased power/ fuel economy and improves drivability.
- Active cleaning agents provide engine cleanliness.

Characteristics:

SILBOIL SCOOTY SPECIAL 4T- NITRIC 10W- 30 SM/MB	
SAE Grade	10W- 30
Viscosity Index, ASTM D 2270	144
cSt @ 100°C	11.4
Total Base #, mg/KOH/g	6.0
Pour Point, °C	-42
Flash Point, °C, ASTM D 92	235

Available Packs:

800 ML, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

POWER 2T- SPECIAL FB/TC

Description:

Silboil Power 2T is an advanced performance two-stroke engine oil developed to meet or exceed the highest level of lubricant requirements by today's highest performance motorcycles, snowmobiles and lean oil/fuel ratio chain saws and other two-stroke applications.

Features:

- Helps to extent life for critical engine parts.
- Long engine life.
- Helps to extend piston life.
- Outstanding overall engine cleanliness.

Characteristics:

SILBOIL POWER 2T- SPECIAL FB/TC	
SAE Grade	Grade-1, 2
Viscosity Index, ASTM D 2270	154
cSt @ 100°C	12.7
Total Base #, mg/KOH/g	5.0
Pour Point, °C	-42
Flash Point, °C, ASTM D 92	100

Available Packs:

500 ML, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

SPECIAL CNG- ADVANCED 20W- 50 SL/CF

Description:

Silboil Special CNG- Advanced is a premium grade gas engine oil specially formulated for automotive engines operating with CNG and LPG as fuels. It is based on superior quality mineral base oil and highly thermally stable additive package for long term protection of engine components. It meets API SL/CF service category.

Features:

- Highly thermally stable additive package offers longer drain interval.
- Excellent hot and cold temperature performance.
- Dissipates heat fast and keeps the engine cool.
- Superior quality base oil provides reduced soot level at high temperatures usually encountered in gas engines.

Characteristics:

SILBOIL SPECIAL CNG- ADVANCED 20W- 50 SL/CF	
SAE Grade	20W- 50
Viscosity Index, ASTM D 2270	125
cSt @ 100°C	17.5 to 18.5
Total Base #, mg/KOH/g	5.0
Pour Point, °C	-21
Flash Point, °C, ASTM D 92	220

Available Packs:

1 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

9894 AIR BRAKE- BRAKE FLUID DOT-4

Description:

Brake and Clutch Fluid DOT 4 is a high performance non-petroleum automotive brake fluid designed for conventional hydraulic brake and clutch systems. Brake and Clutch Fluid DOT 4 is formulated for use under severe operating conditions or where DOT 4 fluids are recommended. Brake and Clutch Fluid DOT 4 combines a complex combination of Polyglycols, Polyglycol Ethers and Glycol Ether Borate Esters, blended with inhibitors designed to prevent corrosion, oxidation and to control seal swell characteristics.

Features:

- Higher and maintained fluid boiling point in service promotes lower vapour formation and greater braking performance than DOT 3.
- Designed to aid vapour lock prevention, offering greater braking safety margin than lower specification fluids.
- Formulated for use in a wide range of conventional systems, reducing inventories and costs.

Characteristics:

SILBOIL 9894 AIR BRAKE- BRAKE FLUID DOT-4	
Colour	Amber
pH value	8.3
cSt @ 100°C	2.2
Equilibrium Reflux Boiling Point, °C	251
Wet Equilibrium Reflux Boiling Point, °C	160
cSt @ -40°C	1296

Available Packs:

100 ML, 250 ML

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

2996 AIR SHOCK- FORK OIL

Description:

Silboil Air Shock- Fork Oil is a specially developed Shock Absorber Fluid for the use in low-friction shock absorbers and spring struts. Highly refined, zero aromatic base oils guarantee excellent viscosity properties at low temperatures. The performance and characteristics are well known and approved by the major shock absorber producers.

Features:

- Extreme Low-Temperature Viscosity Extreme high Viscosity Index.
- High Shear Stability.
- Optimized Wear Protection.
- Excellent Elastomer Compatibility.

Characteristics:

SILBOIL 2996 AIR SHOCK- FORK OIL	
Viscosity Index, ASTM D 2270	190
cSt @ 100°C	3.0 to 4.0
Pour Point, °C	-45
Flash Point, °C, ASTM D 92	130

Available Packs:

175 ML

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

F12S+ COOL OIL- LONGLIFE J1034 1:04

Description:

Silboil F12S+ Cool Oil is a high-performance concentrated antifreeze that is phosphate-free, silicate-free nitrate-free and borate-free ethylene glycol-based coolant that is designed to provide exceptional corrosion protection of all cooling system metals.

Features:

- Maximizes protection of all metals commonly found in the engine cooling systems.
- Keeps engines at optimum operating temperatures contributing to improved fuel economy.
- Excellent protection from cavitation, liner pitting, rust, scale and deposits formation.
- Compatible with ordinary summer coolants.
- Provides year-round cooling properties.
- Protects against excessive evaporation.

Characteristics:

SILBOIL F12S+ COOL OIL- LONGLIFE J1034 1:04	
Appearance	Green
Specific Gravity @ 20°C	1.13
pH	8.5
Reserve Alkalinity,	18
Boiling Point, °C	179
Freezing Point, °C	-18

Available Packs:

1 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

SIL-GUARD MONO LIFE SAE 40 CC/SC

Description:

Silboil Sil-Guard Mono SAE 40 is a heavy-duty monograde engine oil designed for use in heavy-duty low ash engines operating in on- and off- highway service. Formulated with proven quality base stocks, It is designed to meet the specific lubrication requirements of this engine type, and combines detergent, rust and corrosion inhibitors with anti-wear agents for effective engine protection.

Features:

- Engine cleanliness and deposit control.
- Rust and corrosion resistance.
- Maintains oil pressure.

Characteristics:

SILBOIL SIL- GUARD MONO LIFE SAE 40 CC/ SC	
SAE Grade	40
Viscosity Index, ASTM D 2270	109
cSt @ 100°C	14.5
Total Base #, mg/KOH/g	5.0
Pour Point, °C	-24
Flash Point, °C, ASTM D 92	270

Available Packs:

55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

ALL PURPOSE LP-3 ADVANCED

Description:

Silboil All Purpose LP-3 is a premium quality all-purpose automotive grease. Recommended for all types of Wheel bearings used in automobiles e.g. Heavy duty, Light commercial, Passenger vehicles.

Features:

- Excellent thermal and oxidation stability.
- Resistance to water wash out.
- Superior protection against rusting & corrosion.
- Longer bearing life.

Characteristics:

SILBOIL ALL PURPOSE LP-3 ADVANCED	
NLGI	3
Appearance	Smooth and Homogeneous
Colour	Light Yellow
Consistency of the grease @ 25°C Worked, 60 Strokes	200-210
Drop Point, °C	110
Free Alkalinity	0.15
Heat Stability @ 100°C, 30 hrs	3

Available Packs:

100 GM, 200 GM, 500 GM, 1 KG, 2 KG, 3 KG, 5 KG, 10 KG, 18 KG, 170 KG

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

MAGNA PLUS MPLR-3 ADVANCED

Description:

Silboil Magna Plus MPLR-3 Advanced is premium quality grease which is recommended for use in automotive wheel bearing on all types of passenger, commercial vehicles off highway, farm equipment's & high speed automobiles under extreme operating conditions and industrial purposes.

Features:

- Excellent thermal and oxidation stability.
- Resistance to water wash out.
- Superior protection against rusting & corrosion.
- Longer bearing life.

Characteristics:

SILBOIL MAGNA PLUS MPLR-3 ADVANCED	
NLGI	3
Appearance	Smooth and Buttery
Colour	Dark Green
Consistency of the grease @ 25°C Worked, 60 Strokes	220
Drop Point, °C	180
Soap Type	Lithium

Available Packs:

500 GM, 1 KG, 2 KG, 3 KG, 5 KG, 7 KG, 10 KG, 18 KG, 170 KG

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

ULTRA RED GEL GREASE- 2.5 PREMIUM

Description:

Silboil Ultra Red Gel Grease- Premium is a premium quality all-purpose automotive grease. Recommended for all types of Wheel bearings used in automobiles e.g. Heavy duty, Light commercial, Passenger vehicles.

Features:

- Excellent thermal and oxidation stability.
- Resistance to water wash out.
- Superior protection against rusting & corrosion.
- Longer bearing life.

Characteristics:

SILBOIL ULTRA RED GEL GREASE- 2.5 PREMIUM	
NLGI	2.5
Appearance	Smooth and Buttery
Colour	RED
Consistency of the grease @ 25°C Worked, 60 Strokes	250
Drop Point, °C	220
Soap Type	Lithium Methyl

Available Packs:

500 GM, 1 KG, 2 KG, 3 KG, 5 KG, 7 KG, 10 KG, 18 KG, 170 KG

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

HYDRA SAFE HYDRAULIC- 68 AW DIN 51524

Description:

Silboil Hydra Safe Hydraulic- 68 AW is formulated with refined paraffinic base oils. They provide excellent anti-wear protection, oxidation and corrosion inhibition, as well as foam and aeration suppression. All grades have excellent demulsibility characteristics. Hydraulic systems, due to the nature of their operation, experience accelerated wear unless they are protected by clean, high quality anti-wear hydraulic oils. Surging pressures in pumps and valves can increase metal-to-metal contact unless anti-wear protection is present.

Features:

- Good Oxidation Stability.
- Rust and Corrosion Protection.
- Good Foam Inhibition.
- Excellent anti-wear properties.

Characteristics:

SILBOIL HYDRA SAFE HYDRAULIC-68 DIN 51524 AW	
ISO VG	68
Viscosity Index, ASTM D 2270	99
cSt @ 100°C	8.4
Oxidation Stability	> 2000
Pour Point, °C	-22
Flash Point, °C, ASTM D 92	235

Available Packs:

1 Ltr, 5 Ltr, 26 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

HYDRA SAFE HYDRAULIC- 32/46 AW DIN 51524

Description:

Silboil Hydra Safe Hydraulic- 32/46 AW is formulated with refined paraffinic base oils. They provide excellent anti-wear protection, oxidation and corrosion inhibition, as well as foam and aeration suppression. All grades have excellent demulsibility characteristics. Hydraulic systems, due to the nature of their operation, experience accelerated wear unless they are protected by clean, high quality anti-wear hydraulic oils. Surging pressures in pumps and valves can increase metal-to-metal contact unless anti-wear protection is present.

Features:

- Good Oxidation Stability.
- Rust and Corrosion Protection.
- Good Foam Inhibition.
- Excellent anti-wear properties.

Characteristics:

SILBOIL HYDRA SAFE HYDRAULIC-32/46 DIN 51524 AW		
ISO VG	32	46
Viscosity Index, ASTM D 2270	98	98
cSt @ 100°C	5.2	6.5
Oxidation Stability	> 2000	> 2000
Pour Point, °C	-25	-23
Flash Point, °C, ASTM D 92	220	226

Available Packs:

20 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

MAX POWER GEAR BOX OIL EP-90 GL-4

Description: Silboil Max Power Gear Box Oil EP-90 GL-4 is multipurpose gear oils containing extreme pressure additives for moderate service conditions. It is recommended for manual transmissions of automobiles requiring this type of extreme pressure oils.

Features:

- Excellent thermal & chemical stability.
- Protection against rust and corrosion.
- Ensuring longer trouble free operation.

Characteristics:

SILBOIL MAX POWER GEAR BOX OIL EP-90 GL-4	
SAE	90
Viscosity Index, ASTM D 2270	97
cSt @ 100°C	14.5 to 18.0
Copper Strip Corrosion at 121, °C	2
Pour Point, °C	-15
Flash Point, °C, ASTM D 92	230

Available Packs:

500 ML, 1 Ltr, 5 Ltr, 10 Ltr, 20 Ltr, 26 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

MAX POWER GEAR BOX OIL EP-140 GL-4

Description:

Silboil Max Power Gear Box Oil EP-140 GL-4 is multipurpose gear oils containing extreme pressure additives for moderate service conditions. It is recommended for manual transmissions of automobiles requiring this type of extreme pressure oils.

Features:

- Excellent thermal & chemical stability.
- Protection against rust and corrosion.
- Ensuring longer trouble free operation.

Characteristics:

SILBOIL MAX POWER GEAR BOX OIL EP-140 GL-4	
SAE	140
Viscosity Index, ASTM D 2270	97
cSt @ 100°C	24.0- 33.0
Copper Strip Corrosion at 121, °C	2
Pour Point, °C	-9
Flash Point, °C, ASTM D 92	248

Available Packs:

1 Ltr, 5 Ltr, 10 Ltr, 20 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

DSG- DIRECT SHIFT GEAR BOX OIL 80W- 90 GL-5

Description:

Silboil DSG 80W- 90 GL-5 is multigrade gear oil containing extreme pressure additives for moderate condition service Meets API GL -5 , MIL - L - 2105 B and EP Type GL - 5 level of IS: 1118:1992 (Re-affirmed 2008) Application areas are synchromesh transmissions and manual transmissions of automobiles.

Features:

- Excellent thermal & chemical stability.
- Protection against rust and corrosion.
- Ensuring longer trouble free operation.

Characteristics:

SILBOIL DSG- DIRECT SHIFT GEAR BOX OIL 80W- 90 GL-5	
SAE	80W- 90
Viscosity Index, ASTM D 2270	90
cSt @ 100°C	13.5 to 24.5
Copper Strip Corrosion at 121, °C	2
Pour Point, °C	-21
Flash Point, °C, ASTM D 92	165

Available Packs:

1 Ltr, 5 Ltr, 10 Ltr, 20 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

DSG- DIRECT SHIFT GEAR BOX OIL 85W- 140 GL-5

Description:

Silboil DSG 85W- 140 GL-5 is multigrade gear oil containing extreme pressure additives for moderate condition service Meets API GL -5 , MIL - L - 2105 B and EP Type GL - 5 level of IS: 1118:1992 (Re-affirmed 2008) Application areas are synchromesh transmissions and manual transmissions of automobiles.

Features:

- Excellent thermal & chemical stability.
- Protection against rust and corrosion.
- Ensuring longer trouble free operation.

Characteristics:

SILBOIL DSG- DIRECT SHIFT GEAR BOX OIL 85W- 140 GL-5	
SAE	85W- 140
Viscosity Index, ASTM D 2270	90
cSt @ 100°C	26.0 to 32.0
Copper Strip Corrosion at 121, °C	3
Pour Point, °C	-12
Flash Point, °C, ASTM D 92	180

Available Packs:

1 Ltr, 5 Ltr, 10 Ltr, 20 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

UNI-MATIC AUTOMATIC TQ

Description:

Silboil Uni-Matic Automatic TQ is a premium quality red coloured automatic transmission fluid having low static friction properties. It is recommended for use in automatic transmissions & power steering units of automobiles and other LCV'S requiring Dexron II fluids.

Features:

- Better oxidation stability.
- Low temperature viscosity.
- Longer life.
- Seal compatibility.

Characteristics:

SILBOIL DSG- DIRECT SHIFT GEAR BOX OIL 85W- 140 GL-5	
SAE	Allison C4
Colour, Visual	Red
Viscosity Index, ASTM D 2270	187
cSt @ 100°C	5.5
Flash Point, °C, ASTM D 92	200

Available Packs:

1 Ltr, 5 Ltr, 10 Ltr, 20 Ltr, 55 Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

POLO CARE- DEFENDER 10W- 40 SL

Description:

Silboil Polo Care- Defender 10W- 40 is a modern high technology based engine oil exceeding the latest API SL performance specification. Developed to provide maximum protection for use in modern passenger cars including low emission engines and high performance vehicles. It is suitable for all types of driving conditions (city, highway and harsh) and is available in a range of SAE viscosity grades, to meet market conditions. Compatible for all cars running on lead free gasoline and catalytic converters.

Features:

- Helps to extent life for critical engine parts.
- Long engine life.
- Helps to extend piston life.
- Outstanding overall engine cleanliness.

Characteristics:

SILBOIL POLO CARE- DEFENDER 10W- 40 SL	
SAE Grade	10W- 40
Viscosity Index, ASTM D 2270	150
cSt @ 100°C	13.0 to 14.5
Total Base #, mg/KOH/g	9.0
Pour Point, °C	-33
Flash Point, °C, ASTM D 92	100

Available Packs:

1 Ltr, 3.5 Ltr, 4Ltr, 55Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

EXTREME CARE- FORMULA PD 5W- 40 SN/CJ-4

Description:

Silboil Extreme Care- Formula 5W- 40 is an ultra-premium quality, high detergent automotive engine oil specially formulated to meet the stringent lubrication requirements of advanced European automobiles. Synthetic base oils combine with a carefully selected additive package to provide the highest levels of protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish deposits.

Features:

- Outperforms conventional motor oil in high temperature service.
- Provides outstanding thermal and oxidation stability.
- Protects against rust and corrosion.
- Outstanding low temperature performance.

Characteristics:

SILBOIL EXTREME CARE- FORMULA PD 5W- 40 SN/CJ-4	
SAE Grade	5W- 40
API Performance	SN/CJ-4
Viscosity Index, ASTM D 2270	171
cSt @ 100°C	14.2
Total Base #, mg/KOH/g	11
Pour Point, °C	-10
Flash Point, °C, ASTM D 92	210

Available Packs:

3.5 Ltr, 55Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

ENERGY PLUS SCOTT 5W- 30 SM/CH-4

Description:

Silboil Energy Plus Scott is an advanced engine oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. It meets or exceeds the requirements of the industry's toughest standards and outperforms our conventional oils. Its technology comes as standard equipment in many different vehicles, including select high-performance vehicles.

Features:

- Helps prevent deposits and sludge build-up to enable long engine life.
- Aids fuel economy.
- Helps to extend engine life.
- Quick cold weather starting for ultra-fast protection.

Characteristics:

SILBOIL ENERGY PLUS SCOTT 5W- 30 SM/CH-4	
SAE Grade	5W- 30
API Performance	SM/CH-4
Viscosity Index, ASTM D 2270	172
cSt @ 100°C	11.0
Total Base #, mg/KOH/g	9.0
Pour Point, °C	-42
Flash Point, °C, ASTM D 92	230

Available Packs:

1 Ltr, 3 Ltr, 3.5 Ltr, 55Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

FAVORIT PLUS START 15W- 40 SL/CF-4

Description:

Silboil Favorit Plus- Start is a modern high technology based engine oil exceeding the latest API SL performance specification. Developed to provide maximum protection for use in modern passenger cars including low emission engines and high performance vehicles. It is suitable for all types of driving conditions (city, highway and harsh) and is available in a range of SAE viscosity grades, to meet market conditions. Compatible for all cars running on lead free gasoline and catalytic converters.

Features:

- Helps to extent life for critical engine parts.
- Long engine life.
- Helps to extend piston life.
- Outstanding overall engine cleanliness.

Characteristics:

SILBOIL FAVORIT PLUS START 15W- 40 SL/CF-4	
SAE Grade	15W- 40
API Performance	SL/CF-4
Viscosity Index, ASTM D 2270	150
cSt @ 100°C	13.2 to 14.0
Total Base #, mg/KOH/g	8.2
Pour Point, °C	-12
Flash Point, °C, ASTM D 92	180

Available Packs:

3 Ltr, 3.5 Ltr, 55Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111

SILBOIL PRODUCT DATA SHEET

EXCEL PLUS- SPECIAL 20W- 50 SM/CG-4

Description:

Silboil Excel Plus- Special is suitable for use in four-stroke gasoline engines used in passenger cars, light trucks, powerboats, motorcycles, and other mobile and stationary equipment. They are excellent for high-revving engines in small cars and light trucks. All grades are suitable for use in turbocharged engines. They may also be suitable for use in natural gas engines in small cars and light trucks after consulting with the appropriate original equipment manufacturer's lubrication recommendations.

Features:

- Excellent anti-wear protection.
- Energy Savings.
- Meets or exceeds warranty requirements.
- Protection against thermal break down.

Characteristics:

SILBOIL EXCEL PLUS SPECIAL 20W- 50 SM/CG-4	
SAE Grade	20W- 50
API Performance	SM/CG-4
Viscosity Index, ASTM D 2270	121
cSt @ 100°C	18.2
Total Base #, mg/KOH/g	7.4
Pour Point, °C	-24
Flash Point, °C, ASTM D 92	205

Available Packs:

3 Ltr, 3.5 Ltr, 55Ltr, 210 Ltr

Health, Safety, Storage & Environmental:

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.silboil.com, For technical or consumer enquiry mail us at info@silboil.com or call us at +(91)- 7500-067-111