



SIL- GUARD MONO LIFE SAE 40 API CC/SC

Description

Silboil Sil-Guard Mono SAE 40 is a heavy-duty monograde engine oil designed for use in heavy-duty low ash engines operating in on- and off- highway service. Formulated with proven quality base stocks. It is designed to meet the specific lubrication requirements of this engine type, and combines detergent, rust and corrosion inhibitors with anti-wear agents for effective engine protection.

Features

- Engine cleanliness and deposit control.
- Rust and corrosion resistance.
- Maintains oil pressure.

Characteristics

SAE Grade	40
Viscosity Index, ASTM D 2270	109
cSt @ 40°C	14.5
Total Base #, mg/KOH/g	5.0
Pour Point, °C	-24
Flash Point, °C, ASTM D 92	270

*The typical characteristics mentioned represent mean value.



Health & Safety

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

SILBOIL LUBRICANTS (INDIA)

Plot No. 6, Dan Udyog Industrial Estate, Piparia, Silvassa- 396230
Union Territory of Dadra & Nagar Haveli, INDIA

This lubricant used in accordance with our recommendations and for the applications for which it is intended does not represent a special hazard. A Safety data file conforming to the requirements of current Indian legislation is available from your local trade consultant.

For more information, go to www.silboil.com, For technical or consumer support mail us at info@silboil.com or call us at +(91)- 7500-67-111

