



UNIVERSAL 4T-PLUS 20W- 40 API SL MB/MA-2

Description

Silboil Universal 4T- Plus 20W-40 is blended from highly base- stocks with special additive offers extra high performance to impart high oxidation stability, reduce fuel consumption, gear anti-wear, extreme pressure properties, sludge and varnish control. Keeps engine clean and long duration intervals.

Features

- ◆ Exceptional anti-wear properties protect vital engine and gear components leading to reduced maintenance costs.
- ◆ Controlled frictional properties eliminate clutch slippage leading to increased power/ fuel economy and improves drivability.
- ◆ Active cleaning agents provide engine cleanliness.

Characteristics

| | |
|------------------------------|--------------|
| SAE Grade | 20W- 40 |
| Viscosity Index, ASTM D 2270 | 115 |
| cSt @ 40°C | 12.5 to 16.5 |
| Total Base #, mg/KOH/g | 6.0 |
| Pour Point, °C | -20 |
| Flash Point, °C, ASTM D 92 | 205 |

*The typical characteristics mentioned represent mean value.



Health & Safety

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

SILBOIL LUBRICANTS (INDIA)

Plot No. 6, Dan Udyog Industrial Estate, Piparia, Silvassa- 396230
Union Territory of Dadra & Nagar Haveli, INDIA

This lubricant used in accordance with our recommendations and for the applications for which it is intended does not represent a special hazard. A Safety data file conforming to the requirements of current Indian legislation is available from your local trade consultant.

For more information, go to www.silboil.com, For technical or consumer support mail us at info@silboil.com or call us at +(91)- 7500-67-111

